



Barge "SMI-245"
Settoon Towing, LLC
INNAGE TABLE

TANK NO.
1 PORT OF STAR

BARGE SHOULD BE ON EVEN LEVEL, KEEL WHEN GAUGES ARE TAKEN

HULL NO. 008

Table with 14 columns (0 FT. to 14 FT.) and multiple rows. Each cell contains numerical values and unit codes (e.g., 1/4, 1/2, 3/4, 5). The table represents capacity measurements for different tank heights.

CAPACITIES GIVEN IN BARRIELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 8'-4" TO RIM OF 2" DIAMETER BALL VALVE
LOCATED NEAR CENTER OF TANK

STRAPPED: 9/15/03

REISSUED: 7/15/09 TO REFLECT CHANGE IN GAUGE HEIGHT

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



Barge "SML-245"
Settoon Towing, LLC
INNAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 008

TANK NO.
3 PORT or STAR

Table with columns for gauge height (0 FT. to 14 FT.) and rows for capacity (0 to 1541.44). Each cell contains a numerical value representing capacity in gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 8'-4 1/2" (TO RIM OF 2" DIAMETER BALL VALVE

LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 8'-4 5/8" (TO RIM OF 2" DIAMETER BALL VALVE

LOCATED NEAR CENTER OF TANK)

STRAPPED: 9/15/03

REISSUED: 7/18/09 TO REFLECT CHANGE IN GAUGE HEIGHT

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION