





**Barge "SML-295"  
Settoon Towing, LLC  
INNAGE TABLE**

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.
0	5.05	145.36	289.89	424.43	579.34	724.25	868.99	1,011.31	0	0	0	0
1/4	6.86	148.38	292.90	427.45	582.36	727.27	871.98	1,013.50	1/4	1/4	1/4	1/4
1/2	8.67	151.39	295.91	440.47	585.38	730.29	874.96	1,015.69	1/2	1/2	1/2	1/2
3/4	10.47	154.40	298.93	443.49	588.40	733.31	877.95	1,017.88	3/4	3/4	3/4	3/4
1	13.18	157.41	301.93	446.50	591.42	736.33	880.93	1,020.07	1	1	1	1
1/4	15.89	160.42	304.94	449.52	594.44	739.35	883.90	1,021.71	1/4	1/4	1/4	1/4
1/2	18.90	163.43	307.95	452.54	597.45	742.37	886.90	1,023.35	1/2	1/2	1/2	1/2
3/4	21.91	166.44	310.96	455.56	600.47	745.39	889.89	1,024.99	3/4	3/4	3/4	3/4
2	24.92	169.45	313.97	458.58	603.49	748.40	892.87	1,026.64	2	2	2	2
1/4	27.94	172.46	316.97	461.60	606.51	751.42	895.86	1,027.73	1/4	1/4	1/4	1/4
1/2	30.95	175.47	319.98	464.62	609.53	754.44	898.84	1,028.82	1/2	1/2	1/2	1/2
3/4	33.96	178.49	322.99	467.64	612.55	757.46	901.83	1,029.92	3/4	3/4	3/4	3/4
3	36.97	181.50	326.00	470.66	615.57	760.48	904.81	1,031.01	3	3	3	3
1/4	39.98	184.51	329.01	473.68	618.59	763.50	907.80	1,031.56	1/4	1/4	1/4	1/4
1/2	42.99	187.52	332.01	476.69	621.61	766.52	910.78	1,032.11	1/2	1/2	1/2	1/2
3/4	46.00	190.53	335.02	479.71	624.63	769.54	913.77	1,032.65	3/4	3/4	3/4	3/4
4	49.01	193.54	338.03	482.73	627.64	772.56	916.75	1,033.20	4	4	4	4
1/4	52.02	196.55	341.04	485.75	630.66	775.58	919.74	1,033.34	1/4	1/4	1/4	1/4
1/2	55.03	199.56	344.05	488.77	633.68	778.59	922.72	1,033.47	1/2	1/2	1/2	1/2
3/4	58.05	202.57	347.05	491.79	636.70	781.61	925.71	1,033.51	3/4	3/4	3/4	3/4
5	61.06	205.58	350.05	494.81	639.72	784.63	928.69	1,034.04	5	5	5	5
1/4	64.07	208.60	353.07	497.83	642.74	787.65	931.68	1,034.18	1/4	1/4	1/4	1/4
1/2	67.08	211.61	356.08	500.85	645.76	790.67	934.66	1,034.32	1/2	1/2	1/2	1/2
3/4	70.09	214.62	359.09	503.87	648.78	793.69	937.65	1,034.46	3/4	3/4	3/4	3/4
6	73.10	217.63	362.09	506.88	651.80	796.71	940.63	1,034.60	6	6	6	6
1/4	76.11	220.64	365.10	509.90	654.82	799.73	943.62	1,034.74	1/4	1/4	1/4	1/4
1/2	79.12	223.65	368.11	512.92	657.83	802.75	946.60	1,034.88	1/2	1/2	1/2	1/2
3/4	82.13	226.66	371.12	515.94	660.85	805.77	949.59	1,035.02	3/4	3/4	3/4	3/4
7	85.14	229.67	374.13	518.96	663.87	808.78	952.57	1,035.16	7	7	7	7
1/4	88.16	232.68	377.13	521.98	666.89	811.80	955.56	1,035.30	1/4	1/4	1/4	1/4
1/2	91.17	235.69	380.14	525.00	669.91	814.82	958.54	1,035.44	1/2	1/2	1/2	1/2
3/4	94.18	238.71	383.15	528.02	672.93	817.84	961.53	1,035.58	3/4	3/4	3/4	3/4
8	97.19	241.72	386.16	531.04	675.95	820.86	964.51	1,035.72	8	8	8	8
1/4	100.20	244.73	389.17	534.06	678.97	823.88	967.50	1,035.86	1/4	1/4	1/4	1/4
1/2	103.21	247.74	392.17	537.07	681.99	826.90	970.48	1,036.00	1/2	1/2	1/2	1/2
3/4	106.22	250.75	395.18	539.18	685.01	829.92	973.47	1,036.14	3/4	3/4	3/4	3/4
9	109.23	253.76	398.20	543.19	688.02	832.94	976.45	1,036.28	9	9	9	9
1/4	112.24	256.77	401.22	546.13	691.04	835.96	979.44	1,036.42	1/4	1/4	1/4	1/4
1/2	115.25	259.78	404.24	549.15	694.06	838.97	982.42	1,036.56	1/2	1/2	1/2	1/2
3/4	118.27	262.79	407.26	552.17	697.08	841.99	985.41	1,036.70	3/4	3/4	3/4	3/4
10	121.28	265.80	410.28	555.19	700.10	845.01	988.39	1,036.84	10	10	10	10
1/4	124.29	268.82	413.30	558.21	703.12	848.03	991.38	1,036.98	1/4	1/4	1/4	1/4
1/2	127.30	271.83	416.31	561.23	706.14	851.05	994.36	1,037.12	1/2	1/2	1/2	1/2
3/4	130.31	274.84	419.33	564.25	709.16	854.07	997.35	1,037.26	3/4	3/4	3/4	3/4
11	133.32	277.85	422.35	567.26	712.18	857.05	1,000.36	1,037.40	11	11	11	11
1/4	136.33	280.86	425.37	570.28	715.20	860.04	1,003.10	1,037.54	1/4	1/4	1/4	1/4
1/2	139.34	283.87	428.39	573.30	718.21	863.02	1,005.83	1,037.68	1/2	1/2	1/2	1/2
3/4	142.35	286.88	431.41	576.32	721.23	866.01	1,008.57	1,037.82	3/4	3/4	3/4	3/4

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 8'- 5" (TO RIM OF BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 1/17/11

WE CERTIFY ALL  
IN ACCORDANCE  
ARE TRUE AND  
INSPECTORATE

