



Barge "SMI-30018" Settoon Towing, LLC INNAGE TABLE

TANK NO. 1 PORT or STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. C-909

Table with columns for depth (0 FT. to 14 FT.) and corresponding capacity values for various tank sections.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 9/9/10

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT: 15'-8 1/2" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name



Barge "SMI-30018" Settoon Towing, LLC INNAGE TABLE

TANK NO. 3 PORT or STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. C-909

Table with columns for height (0 FT. to 14 FT.) and capacity (N, 1/4, 1/2, 3/4). Includes a row for 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' and a 'STRAPPED: 9/9/10' note.

* CAPACITY BELOW STRIKE POINT.

PORT REFERENCE GAUGE HEIGHT : 15'-8 1/2" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-9" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name