



Bolivar Barge Cleaning Service, LLC

CARGO HOSE/PIPING INSPECTION AND TESTING REPORT

REGULATION: "The cargo hose and piping shall be hydrostatically tested at least once each year to 1-1/2 times its maximum allowable working pressure. The maximum allowable working pressure shall be stenciled on the cargo hose and piping."

FREQUENCY: Required at least once a year for compliance with 33 CFR 156.170.

LOCATION: Gov. Murrings Pt. Bolivar SERIAL# SMI 30048

DATE: 7-6-2016

MAXIMUM ALLOWABLE WORKING PRESSURE 125 PSIG

HOSE TEST PRESSURE
(1-1/2 Times Maximum Allowable psig) 187.5 PSIG

MAXIMUM ALLOWABLE PRESSURE STENCILED

ON HOSE _____ PSIG

ON PIPING 125 PSIG

OTHER EQUIPMENT TESTED

_____ PSIG

_____ PSIG

_____ PSIG

REMARKS

SIGNATURE JAM

**BOLIVAR BARGE CLEANING SERVICES,LLC
PO.BOX 1315
SANTA FE ,TEXAS 77510
409-925-8897**

VAPOR TIGHTNESS TEST

**DATE __7-6-2016_
VESSEL SMI 30048
OWNER SETTOON TOWING
PO.BOX 279
PIERRE PART LA. 70339**

Barge is vapor tight if “Total Pressure Loss is LESS than Allowable Pressure loss.

Tested with ERL Guage.

**Beginning Pressure 1-1/2 psi
Ending Pressure 1-1/2psi
Total Loss pressure 0 psi**

**THE FOLLOWING BARGE WAS TESTED IN ACCORDANCE WITH THE
NATIONAL EMISSION STANARD FOR BENZENE EMISSIONS FROM BENZENE
TRANSFER OPERATIONS,SECTION 40CFR61.604(F)AND SECTION 40 CFR
63.565(C)**

TESTER NAME Bubba Gates

TESTER SIGNATURE

